

SPECIFICATIONS

Precise 100



Precise 100 SC BioKeyboard

FEATURES

- Ease of use
- Real-time image capturing
- Precise Match-on-Card™ enabled
- Precise BioMatch™ Standard enabled
- Plug'n'Play installation¹
- Unique ergonomic design
- Dual-color LED indicator for user interaction

TECHNICAL SPECIFICATIONS

General

- Size: 572 x 195 x 45 mm / 22.5 x 7.7 x 1.8 inches (L x W x H)
- Power consumption: Max 270 mA
- Operating temperature range: 0-50° Celsius / +32 to 120°F
- FCC (Part 15 Class B) and CE certified
- ISO9002 production certified
- Drivers: Windows® XP (USB only)
Windows® 2000
Windows® NT 4.0 (parallel port only)
Windows® 98 (USB only)
Windows® Me (USB only)

Biometric Reader

- Silicon fingerprint sensor
- Image encryption
- Parallel port or USB connection

Smart Card Reader

- All ISO/IEC 7816 compatible cards supported
- PC/SC driver supports T=0 and T=1

Keyboard

- Membrane key switch
- 20 Windows Multimedia keys
- Universal Language
- PS/2 connection

SYSTEM REQUIREMENTS

- Windows® XP, Windows® 2000, Windows® NT 4.0 (Service Pack 6), Windows® 98 (Service Pack 1), Windows® 98 SE or Windows® ME
- ECP-compatible parallel port or USB port
- Precise BioMatch™ enabled application, based on Precise Match-on-Card™, BioAPI, HA-API or BNX API

¹ USB

All specifications are subject to change without notice.



www.precisebiometrics.com

Sweden: Precise Biometrics AB, Scheelevägen 19 C, SE-223 70 Lund
Phone: +46 46 311 100 Fax: +46 46 311 101 info@precisebiometrics.com

Precise Biometrics AB, Finlandsgatan 66 2nd floor, SE-164 74 Kista
Phone: +46 8 632 33 50 Fax: +46 8 632 33 55 info@precisebiometrics.com

USA: Precise Biometrics Inc, 8300 Boone Boulevard, Suite 500 Vienna, VA 22182
Phone: +1 (703) 848-9266 Fax: +1 (703) 832-0577 infous@precisebiometrics.com